



---

## AAI-OBVP-7500 PDU Specification

The American Power Systems OBVP series PDU delivers 7500 VA of clean, regulated AC power in a ruggedly built chassis designed to meet the rigors of military vehicle power. The VIN Inverter is designed to meet military standards and multiple units can be paralleled for additional power.

### INPUT

Voltage: 24 VDC +20%, - 10%  
Incorporates volt surge protection IAW MIL-STD-1275

### OUTPUT

Power: 7500 VA  
Voltage: 120/208 VAC, 3 Phase, Isolated and Floating  
(Other voltages available)  
Frequency: 50, 60 & 400 Hz switch selectable  
Current: 21 Amps/phase  
Current Crest Factor: 3:1  
Power Factor: 100% of rated output into any power factor load.  
Distortion: 3.0% THD typical  
Load Regulation: +/- 1.0% No Load to Full Load.  
Line Regulation: " 0.1% for " 10% Line Change  
Efficiency: 85% typical.

### PROTECTIVE CIRCUITS:

Input Protection: Circuit breaker.  
Constant Current Mode: Overload automatically causes voltage fold back to provide maximum current without distorting output waveform.  
Short Circuit Protection: Short Circuit electronically latched output open to protect load. Power restored by recycling circuit breaker.  
Thermal Protection: Internal temperature sensor prevents heat damage.

### MECHANICAL SPECIFICATIONS: Ruggedly built bulkhead mount enclosure.

Dimensions: 10.5"H x 17"W x 22"D.  
Weight: 50 lbs.  
Cooling: Internal fans  
Operating Temperature: 0 to 50° C.  
Storage Temperature: -20 to 70° C  
Humidity: 0-95% RH non-condensing.  
Input Connections: MIL connector (TBD)  
Output Connections: MIL connector (TBD)

## **SPECIAL FEATURES:**

- **Switch selectable frequencies of 50 Hz, 60 Hz and 400 Hz.**
- **Multiple units can be wired in Parallel for higher power requirements.**
- **Designed to meet the rigors of vehicle power**
- **Designed to meet the following MIL standard's**
  - Shock: MIL-S-901; MIL-STD-810**
  - Vibration: MIL-STD-167; MIL-STD-810; RTCA/DO-160**
  - Humidity: MIL-STD-810**
  - EMI/EMC: MIL-STD-461C/D; RE102 with proper shielding.**

### **World Headquarters**

3750 West River Drive, Davenport, IA 52802  
(563)323-7994 Fax(563)323-7994

## ***American Armature***

e-mail: [sales@americanarmature.com](mailto:sales@americanarmature.com)  
Web-site: [www.americanarmature.com](http://www.americanarmature.com)

AAI-OBVP-7500