# CONVERTERS MODEL Stepdown | PART #APS-28DN12-80 28V down 12V | 80 amps



#### **FEATURES & BENEFITS**

- Wide input voltage range
- Stable output voltage (12VDC)
- 100% full-rated power
- 100% burn-in test
- High efficiency up to 95%
- Overcurrent, overvoltage & overtemperature protection
- Cooling by free air convection
- Surface mountable
- IP68 waterproof
- Epoxy potting
- Anti-vibration
- Dustproof

### **APPLICATIONS**

Decreased output voltage means the enduser can operate equipment that requires a regulated 12-volt DC power source from a system operating at 24 volts DC, a common scenario for military and recreational vehicles and many marine applications.



## **GENERAL AND MECHANICAL SPECIFICATIONS**

#### VARIANT

Weight	1.9 kg
Dimensions (LxWxH)	180x127x63 mm
Input Voltage Range (VDC)	21-35VDC
Output Voltage (VDC)	12VDC
Output Current	80 amps
Output Power Maximum	960 watts
Ripple & Noise Type (mVp-p)	200mVp
Efficiency	95%

All specifications measured at 25 C, nominal input voltage, and full load unless otherwise noted.



426 West Second Street | Davenport, Iowa 52801 +1 (563) 323-7994 | sales@americanpowerinc.com www.americanpowerinc.com Revised April 2022

© 2022 American Power Systems, Inc. ®