



Testing conditions completed at 100°C in a hot box to more closely simulate real-world use.

100°C	Wattage	Wattage	Wattage	Wattage	Wattage	Wattage
Alt RPM	130a-24v	130a-48v	160a-48v	185a-24v	255a-12v	360a-12v
Tested at	26.6vdc	53.2vdc	53.2vdc	27.4vdc	13.7vdc	13.7vdc
1280	159.6					
1288					164.4	
1500	824.6					
1513						
1780						150.7
1800					1438.5	
1893				137		
2000	1862			438.4	1657.7	986.4
2128						
2475		319.2				
2500	2420.6	478.8		2082.4	2000.2	1986.5
3000	2713.2	2447.2		2822.2	2233.1	2534.5
3370		3511.2				
3390			319.2			
3500	2846.2	3830.4	798	3452.4	2424.9	2794.8
3590	2926.0					
4000	2952.6	4681.6	3138.8	3726.4	2520.8	3027.7
4500	2979.2	5160.4	4628.4	3973	2466.0	3109.9
5000	2979.2	5426.4	5426.4	4027.8	2548.2	3219.5
5500	3005.8	5426.4	6064.8	4164.8	2575.6	3288.0
6000	3005.8	5586.0	6596.8	4274.4	2603.0	3507.2
6500	3005.8	5692.4	6916.0	4356.6	2466.0	3603.1
7000	3005.8	5745.6	7182.0	4384.0	2466.0	3644.2
7500	3005.8	5745.6	7394.8	4438.8	2466.0	3685.3
8000	3005.8	5745.6	7554.4	4466.2	2493.4	3562.0
8500	3005.8	5745.6	7660.8	4521.0	2534.5	3616.8
9000	3005.8	5745.6	7660.8	4548.4	2479.7	3616.8