



Testing conditions completed at 100°C in a hot box to more closely simulate real-world use.



High Output Alternators - UPI Series

100°C	Wattage	Wattage	Wattage	Wattage	Wattage	Wattage
Alt RPM	165a-24v	240a-24v	230a-48v	170a-48v	290a-12v	390a-12v
Tested at	26.6	26.6	53.2	53.2	13.3	13.3
1182					70.5	
1208	53.2					
1376	611.8					
1567		199.5				
1596	1409.8					
1674					1489.6	172.9
1800	1755.6	1250.2			1635.9	665.0
2000	2021.6	2048.2			1848.7	1396.5
2251				159.6		
2500	2420.6	3085.6		1649.2	2008.3	2247.7
3000	2580.2	3670.8		3617.6	2114.7	2633.4
3213			106.4			
3500	2686.6	3857.0	1702.4	4575.2	2247.7	2872.8
4000	2766.4	4043.2	4362.4	5213.6	2274.3	2926.0
4500	2899.4	4176.2	5586.0	5532.8	2314.2	3112.2
5000	2926.0	4282.6	6171.2	5798.8	2327.5	3192.0
5500	2979.2	4309.2	6650.0	5905.2	2354.1	3138.8
6000	3059.0	4309.2	7075.6	6064.8	2367.4	3205.3
6500	3059.0	4548.6	7448.0	6171.2	2380.7	3258.5
7000	3112.2	4628.4	7714.0	6277.6	2394.0	3245.2
7500	3138.8	4655.0	7820.4	6277.6	2420.6	3325.0
8000	3165.4	4681.6	8033.2	6437.2	2394.0	3551.1
8500	3165.4	4681.6	8192.8	6490.4	2487.1	3577.7